AIRR:ARR-2026-0TQG72VXJ39KWVNJ v1 [Mathematical physics] 27 Nov 2026 · AIRR.SCIENCE

Sub-Unit Uniform Gate Lifting, the $\frac{1493}{1680}$ PSPACE-Completeness Density Threshold, Kawamura-Dual Barriers, and C_5 Prime-Assignment Optimality for Pinwheel Scheduling

Lluis Eriksson
Independent Researcher
github.com/lluiseriksson/paper138-pinwheel-pspace-density-gate-lifting

November 27, 2026

Abstract

In a landmark breakthrough settling a 37-year-old open problem of Holte, Mok, Rosier, Tulchinsky, and Varvel [2], Fotakis, Kanellopoulos, Mitropoulos, Pagourtzis, Papadimitriou, Pergaminelis, and Tolias [1] proved that binary-encoded Pinwheel Scheduling is PSPACE-complete, even when the instance density $\rho = \sum_i 1/d_i$ lies arbitrarily close to 1 ($1-\varepsilon < \rho < 1$). Combined with Kawamura's resolution of the 5/6 density conjecture [3] ($\rho \le 5/6$ is always schedulable), this left the entire density interval $(5/6, 1-\varepsilon)$ open.

We establish four sharp, machine-checked structural advances, backed by 20 constructive Lean 4.36.0 theorems (zero `sorry`, zero `Classical.choice`, zero external imports) and an AST-audited zero-float exact-rational verifier generating 16 SHA-256 certificates and passing 56 adversarial tests:

1. **Sub-Unit Uniform Gate Lifting & PSPACE-Completeness Down to $\frac{1493}{1680}$ (≈ 0.88869).** We introduce *uniform c-gates*—Pinwheel bases admitting a c-periodic schedule with one idle slot per c slots while enforcing idle-slot separation $\xi_{j+1} - \xi_j \ge c$ across every bi-infinite feasible schedule—and prove a general Gate-Lifting Theorem lifting any saturated break-free Daily Scheduling instance $\mathcal{D}$ to Pinwheel instances with exact density $\rho(P_G(\mathcal{D})) = \rho(G) + \frac{1}{c} - \sum_i \frac{c\delta_i}{Tb_i(Tb_i+c\delta_i)}$. Certifying the full 840-state age automaton (98-state bi-infinite core, unique idle source) of $G_4 = (3,4,7,10)$ ($c = 16$, $\rho(G_4) = \frac{347}{420} < \frac{5}{6}$) directly inside the Lean 4 kernel (`thm14`), we prove that Pinwheel Scheduling is PSPACE-complete for every $\varepsilon > 0$ on instances satisfying $\frac{1493}{1680} - \varepsilon < \rho < \frac{1493}{1680}$—closing $\frac{187}{280} \approx \mathbf{66.79}\%$ of the open $(5/6, 1)$ Fotakis–Kawamura density gap (with intermediate ladders $G_2 = (2,5)$ at $\frac{19}{20}$ and $G_4' = (3,5,6,7)$ at $\frac{389}{420}$).
2. **Kawamura-Dual Gate Barrier & Exact $(2, 2m+1)$ Forced-Occupancy Law.** We prove that every feasible Pinwheel base B with asymptotic idle frequency $\lambda_{\max}(B)$ obeys $\rho(B) + \lambda_{\max}(B) \ge \frac{5}{6}$ (ruling out any gate lifting below 5/6), and derive the exact closed-form $(2, 2m+1)$ forced-occupancy excess $\Phi(2, 2m+1) = \frac{1}{2m(2m+1)}$ with constructive $2m$-window uniformity (attaining $\frac{5}{6}$ at $m = 1$ and $\frac{19}{20}$ at $m = 2$, contrasting with zero excess on $(2, 2m)$).
3. **Uniqueness of C_5 and Pareto-Optimal Prime Assignments.** We prove that C_5 and $K = 2310$ are minimal for width-2 rigid-vs-moving separation in Stage 2 of [1], and exhaustively audit all $5! = 120$ bijections of $\{2,3,5,7,11\}$ onto the non-edges of C_5, uncovering a strictly filler-optimal assignment $(6, 21, 77, 55, 10)$ (3822 vs. 4002 fillers, saving 180 jobs per two-hour test) and a period-optimal assignment $(10, 35, 21, 33, 22)$ ($\max c_v = 35$ vs. 55).

4. **Exact Slack Conservation and Minimal 5-Slot Obstruction for $(3,4,4,d) \to \frac{5}{6}^+$.** We prove exact two-sided slack identities for gate-lifted reductions and certify via exhaustive kernel verification that $(3,4,4,d)$ (all deadlines ≥ 3, density $\frac{5}{6} + \frac{1}{d} \to \frac{5}{6}^+$) is infeasible for every $d \geq 1$ on a minimal 5-slot local window $\{-2,-1,0,1,2\}$.

1 Introduction

In *Pinwheel Scheduling* [2], we are given positive integer deadlines $(d_1, \ldots, d_n)$ and must decide whether there exists an infinite schedule $S : \mathbb{N} \to \{0, 1, \ldots, n\}$ (one job per slot, or idle 0) such that every job i appears at least once in every d_i consecutive slots. Because the age vector $(a_1, \ldots, a_n) \in \prod_i \{0, \ldots, d_i - 1\}$ takes finitely many states, feasibility is equivalent to the existence of a *bi-infinite periodic* feasible schedule $S : \mathbb{Z} \to \{0, 1, \ldots, n\}$ [2, 1].

Two landmark theorems frame the modern complexity landscape of Pinwheel Scheduling as a function of the total density $\rho := \sum_{i=1}^{n} \frac{1}{d_i}$:

- **Low-density tractability (Kawamura [3]):** Every instance with $\rho \leq \frac{5}{6}$ is feasible (decidable in $O(1)$ time), matching the classic infeasible family $(2,3,d)$ at $\rho = \frac{5}{6} + \frac{1}{d} \to \frac{5}{6}^+$.
- **High-density PSPACE-completeness (Fotakis et al. [1]):** Binary-encoded Pinwheel Scheduling is PSPACE-complete via a three-stage reduction from Periodic 3-SAT [6] through Daily Scheduling with Breaks and break-free Daily Scheduling, yielding hard instances with density $1 - \varepsilon < \rho < 1$ (whereas $\rho = 1$ is NP-complete [2, 4, 5]).

This leaves an immediate, sharply defined structural question: *how far into the open density interval* $(\frac{5}{6}, 1)$ *does* PSPACE*-completeness penetrate, what fundamental barrier governs sub-unit density lifting, and are the core combinatorial gadgets of [1] optimal?* We answer all three questions with fully machine-checked proofs.

2 Sub-Unit Uniform Gate Lifting and PSPACE-Completeness at $\frac{1493}{1680}$

In Stage 3 of [1], a saturated break-free Daily Scheduling instance $\mathcal{D} = (w, \{(b_i, \delta_i)\}_{i=1}^n)$ ($\sum_{i=1}^n 1/b_i = w$, $\Delta = \max_i \delta_i$, $b^* = \max_i b_i$, $L = \operatorname{lcm}_i b_i$) is embedded into Pinwheel Scheduling using wk dyadic clock jobs of deadlines $w2^h$ $(h = 1, \ldots, k)$, whose combined density $1 - w/T$ forces total density $\rho \to 1^-$. We break this unit-density barrier by replacing the implicit 1-slot carrier with a rigid *uniform c-gate* whose forced occupancy strictly exceeds its own density.

Definition 2.1 (Uniform c-Gate)**.** A Pinwheel tuple $G = (g_1, \ldots, g_r)$ is a *uniform c-gate* ($c \geq 2$) if:

1. *(c-periodic template)* G admits a c-periodic feasible schedule leaving exactly one idle slot per c slots (placed on $c\mathbb{Z}$); and
2. *(Bi-infinite c-window capacity)* In every feasible bi-infinite schedule of G (with all non-G jobs treated as idle), any two idle slots $\xi_j < \xi_{j+1}$ satisfy $\xi_{j+1} - \xi_j \geq c$.

Theorem 2.2 (Sub-Unit Uniform Gate-Lifting Theorem)**.** *Let $G = (g_1, \ldots, g_r)$ be a uniform c-gate, and let $\mathcal{D} = (w, \{(b_i, \delta_i)\}_{i=1}^n)$ be a saturated break-free Daily Scheduling instance ($\sum_{i=1}^n 1/b_i = w$, $\Delta = \max_i \delta_i$, $b^* = \max_i b_i$, $L = \operatorname{lcm}_i b_i$). Set $\Omega := Lw^n + 6L + 10$, $E' := \Omega(c\Delta + 1)(n(b^* + 1) + w)$, and choose $k \in \mathbb{N}$ so that $T := cw2^k > \max(c\Delta,\, n(2E' + 3))$ (noting $\log \Omega = \operatorname{poly}(\log L, n, \log w)$ so k and all deadline bit-lengths remain polynomial). Define the Pinwheel instance $P_G(\mathcal{D})$ consisting of:*

- *the r gate jobs $G = (g_1, \ldots, g_r)$,*

- *wk dyadic clock jobs (w copies of deadline $cw2^h$ for each $h = 1, \dots, k$), and*
- *n payload jobs of deadline $d_i := Tb_i + c\delta_i$ $(i = 1, \dots, n)$.*

Then $\mathcal{D}$ is feasible if and only if $P_G(\mathcal{D})$ is feasible, and its exact density satisfies (arithmetic cores in Lean `thm03`–`thm04`, `thm08`–`thm10`, *Cert.* `C08`*):*

$$\rho(P_G(\mathcal{D})) \;=\; \rho(G) + \frac{1}{c} - \sum_{i=1}^{n} \frac{c\delta_i}{Tb_i(Tb_i + c\delta_i)} \;\in\; \left[\rho(G) + \frac{1}{c} - \frac{nc\Delta}{T^2},\;\; \rho(G) + \frac{1}{c}\right). \tag{1}$$

Proof. **Density identity:** The wk clock jobs have combined density $\sum_{h=1}^{k} \frac{w}{cw2^h} = \frac{1}{c} - \frac{1}{c2^k} = \frac{1}{c} - \frac{w}{T}$. Since $\sum_{i=1}^{n} \frac{1}{b_i} = w$, we have $\frac{w}{T} = \sum_{i=1}^{n} \frac{1}{Tb_i}$, and $\frac{1}{Tb_i} - \frac{1}{Tb_i + c\delta_i} = \frac{c\delta_i}{Tb_i(Tb_i + c\delta_i)}$ (Lean `thm03`), yielding (1) directly; since $b_i \geq 1$ and $0 \leq \delta_i \leq \Delta$, each term is bounded above by $\frac{c\delta_i}{T^2 b_i^2} \leq \frac{c\Delta}{T^2}$ (Lean `thm04`).

Completeness ($\mathcal{D} \implies P_G(\mathcal{D})$): Place the c-periodic template of G on $\mathbb{Z} \setminus c\mathbb{Z}$, leaving the subgrid $c\mathbb{Z}$ completely free. Partition $c\mathbb{Z}$ into blocks of w consecutive slots of span cw indexed by $z \in \mathbb{Z}$ (each block holds slots $\{cwz + cy : 0 \leq y < w\}$). For each level $h \in \{1, \dots, k\}$, assign the w clock jobs of deadline $cw2^h$ to the blocks $z \equiv 2^{h-1} \pmod{2^h}$, achieving exact gap $cw2^h$. The remaining blocks $z \equiv 0 \pmod{2^k}$ lie at positions $Tt + cy$ $(t \in \mathbb{Z},\ 0 \leq y < w)$. Place each Daily Scheduling job i scheduled on day t at hour $y_i(t) \in \{0, \dots, w-1\}$ into slot $Tt + cy_i(t)$. Whenever job i runs on days t and $t + b_i$ with $y_i(t + b_i) - y_i(t) \leq \delta_i$, its Pinwheel gap is $(T(t + b_i) + cy_i(t + b_i)) - (Tt + cy_i(t)) \leq Tb_i + c\delta_i = d_i$ (Lean `thm08`).

Soundness ($P_G(\mathcal{D}) \implies \mathcal{D}$): If $P_G(\mathcal{D})$ is feasible, by finite-state pigeonhole on the combined age vector it admits a bi-infinite periodic feasible schedule $S : \mathbb{Z} \to \{0, 1, \dots, r + wk + n\}$. Treating all non-$G$ jobs as idle gives a bi-infinite feasible schedule of G, so by Definition 2.1(2) the surviving non-G slots $\xi_j^{(0)}$ satisfy $\xi_{j+1}^{(0)} - \xi_j^{(0)} \geq c$, hence $\xi_{j+w}^{(0)} - \xi_j^{(0)} \geq cw$ (Lean `thm09`). Inductively deleting the w level-h clock jobs $(h = 1, \dots, k)$ exactly as in Lemma 5.3 of [1] doubles the w-step spacing at each level (Lean `thm09`), proving that the remaining payload slots x_j satisfy $x_{j+w} - x_j \geq cw2^k = T$. Now apply Lemmas 5.5–5.8 of [1] verbatim with scaled ascent budget $\Delta' = c\Delta$: averaging forward-gap deviations over ΩT slots bounds total deviation by E'; pigeonhole selects a day-cut γ mod T avoiding n cyclic intervals of radius E' $(n(2E' + 1) < T)$; saturation forces exactly w payload slots per retained day with monotone within-day offsets $\eta_{t+1,y} \geq \eta_{t,y}$; and because consecutive surviving slots satisfy $\eta_{t,y+1} - \eta_{t,y} \geq c$, any upward shift of a hours costs $\eta_{t,y+a} - \eta_{t,y} \geq ca$ (Lean `thm09`–`thm10`), so $ca \leq c\delta_i$ forces $a \leq \delta_i$, reconstructing a valid schedule for $\mathcal{D}$. □

Theorem 2.3 (Machine-Checked Sub-Unit Uniform Gates & PSPACE-Completeness at $\frac{1493}{1680}$)**.** *The following three Pinwheel tuples are certified uniform c-gates (Lean* `thm11`–`thm14`, *Certs.* `C01`–`C04`*):*

1. $G_2 = (2, 5)$ *is a uniform 4-gate (bi-infinite core: 7 of 10 states; cycle* `_121`*; $\rho = \frac{7}{10}$; lifted ceiling $\frac{19}{20} = 0.95$).*
2. $G_4' = (3, 5, 6, 7)$ *is a uniform 12-gate (core: 76 of 630 states; cycle* `_31241231421`*; $\rho = \frac{59}{70}$; lifted ceiling $\frac{389}{420} \approx 0.92619$).*
3. $G_4 = (3, 4, 7, 10)$ *is a uniform 16-gate (core: 98 of 840 states; unique idle source in core; cycle* `_123142131241321`*; $\rho = \frac{347}{420} < \frac{5}{6}$; lifted ceiling $\frac{1493}{1680} \approx 0.88869$).*

Consequently, for every $\varepsilon > 0$, binary-encoded Pinwheel Scheduling restricted to instances of density $\frac{1493}{1680} - \varepsilon < \rho < \frac{1493}{1680}$ is PSPACE-complete, closing $\frac{187}{280} > \frac{2}{3}$ (66.79%) of the open $(\frac{5}{6}, 1)$ gap between Kawamura [3] and Fotakis et al. [1].

Proof. For each gate $G = (g_1, \dots, g_r)$, consider its finite age-state automaton on $Q = \prod_{j=1}^{r} \{0, \dots, g_j - 1\}$. To certify Property (2) of Definition 2.1 unconditionally in the Lean 4 kernel, we assign each state $u \in Q$ an integer tag $\mathrm{tag}(u)$ encoding three disjoint regions:



Figure 1: (a) Pinwheel Scheduling density phase diagram showing Kawamura's $\rho \le 5/6$ always-YES region, Fotakis et al.'s 1^- hardness, and our gate-lifted PSPACE-completeness thresholds 19/20, 389/420, and 1493/1680, closing 66.8% of the open $(5/6, 1)$ gap. (b) Exact 16-slot periodic schedule of the champion uniform 16-gate $G_4 = (3, 4, 7, 10)$ (core = 98 states, $\rho = 347/420 < 5/6$).

Table 1: Machine-checked uniform c-gate hierarchy for Pinwheel Scheduling (Lean `thm12`–`thm14`, `thm20`, Certs. `C01`–`C04`).

Gate Tuple G	Period c	Core / States	Base $\rho(G)$	Lifted $\rho(G) + \frac{1}{c}$	Decimal	Gap Closed
Empty $(\emptyset, [1])$	1	1/1	0	1	1.00000	0.0%
$G_2 = (2, 5)$	4	7/10	7/10	19/20	0.95000	30.0%
$G'_4 = (3, 5, 6, 7)$	12	76/630	59/70	389/420	0.92619	44.3%
$G_4 = (3, 4, 7, 10)$	16	98/840	347/420	**1493/1680**	**0.88869**	**66.8%**

- $\mathrm{tag}(u) < 1000$: finite forward-extinction rank ($\mathrm{tag}(v) < \mathrm{tag}(u)$ on every valid outgoing edge $u \to v$), so by well-founded descent (Lean `thm11`) no infinite forward walk can touch u;
- $1000 \le \mathrm{tag}(u) < 2000$: finite backward-extinction rank within forward-alive states (every predecessor $w \to u$ satisfies $\mathrm{tag}(w) < 1000$ or $\mathrm{tag}(w) < \mathrm{tag}(u)$), so no bi-infinite valid walk can touch u;
- $\mathrm{tag}(u) \ge 2000$: state lies in the bi-infinite recurrent core with idle-distance potential $\mathrm{pot}(u) := \mathrm{tag}(u) - 2000$, satisfying (a) for every idle transition $s \xrightarrow{0} t$ in core, $\mathrm{pot}(s) = 0$ and $\mathrm{pot}(t) \ge c-1$; and (b) for every non-idle transition $u \to v$ in core, $\mathrm{pot}(u) \le \mathrm{pot}(v) + 1$.

By induction on path length (Lean `thm11`), any non-idle path of length L starting at t ends at a state w with $\mathrm{pot}(w) + L \ge \mathrm{pot}(t) \ge c - 1$; reaching any idle source (pot = 0) therefore requires $L \ge c - 1$, proving $\xi_{j+1} - \xi_j \ge 1 + (c-1) = c$ on every bi-infinite feasible schedule. All state tags and c-periodic cycles for G_2, G'_4, and G_4 are checked exhaustively by kernel reduction in Lean `thm12`–`thm14` and Certs. `C01`–`C03`. Combining Theorem 2.2 for G_4 with Stages 1–2 of [1] (increasing k by $O(\log(nc\Delta/\varepsilon))$ so $nc\Delta/T^2 < \varepsilon$) yields PSPACE-completeness in $(\frac{1493}{1680} - \varepsilon, \frac{1493}{1680})$, with gap closure $(1 - \frac{1493}{1680})/(1 - \frac{5}{6}) = \frac{187}{280} > \frac{2}{3}$ (Lean `thm20`). □

3 Kawamura-Dual Gate Barrier and the Exact $(2, 2m+1)$ Forced-Occupancy Law

Can sub-unit uniform gate lifting push below $\frac{5}{6}$? And what exact excess $\Phi(B) := (1 - \lambda_{\max}(B)) - \rho(B)$ drives sub-unit ceilings? We establish a universal dual barrier and a closed-form law for all two-job instances $(2, d)$.

Theorem 3.1 (Kawamura-Dual Gate Barrier and Exact $(2, d)$ Forced-Occupancy Law)**.** *Let $\lambda_{\max}(B)$ denote the supremum asymptotic frequency of idle slots across all feasible schedules of a Pinwheel base B.*

1. ***Universal Dual Barrier (arithmetic core in Lean `thm20`, Cert. `C07`):*** *Every feasible Pinwheel base B satisfies $\rho(B) + \lambda_{\max}(B) \geq \frac{5}{6}$. In particular, no uniform c-gate can achieve $\rho(G) + \frac{1}{c} < \frac{5}{6}$.*
2. ***Exact $(2, 2m+1)$ Forced-Occupancy Law (Lean `thm05`–`thm07`, Certs. `C05`–`C06`):*** *For every integer $m \geq 1$, the even family $(2, 2m)$ has $\lambda_{\max}(2, 2m) = \frac{m-1}{2m}$ with zero excess ($\rho + \lambda_{\max} = 1$), whereas the odd family $(2, 2m+1)$ satisfies*

$$\lambda_{\max}(2, 2m+1) = \frac{m-1}{2m}, \qquad \Phi(2, 2m+1) = \frac{1}{2m(2m+1)},$$
$$\rho(2, 2m+1) + \lambda_{\max}(2, 2m+1) = 1 - \frac{1}{2m(2m+1)}, \tag{2}$$

with constructive $2m$-window uniformity: every $2m$ consecutive slots of any feasible bi-infinite schedule of $(2, 2m+1)$ contain at most $m-1$ idle slots, attained by the $2m$-periodic schedule $(1, _)^{m-1}, (1, 2)$.

Proof. (1) Suppose for contradiction that some feasible base B had $\rho(B) + \lambda_{\max}(B) < \frac{5}{6}$. Writing rational approximations $r/Q \geq \rho(B)$ and $\ell/Q \geq \lambda_{\max}(B)$ with $6(r + \ell) < 5Q$ (or exact rationals since $\lambda_{\max}(B)$ is achieved by a maximum-mean cycle of B's finite automaton), set $D := 6Q$ and $k := 6\ell + 1$ (Lean `thm20`). Then $\frac{k}{D} > \frac{\ell}{Q} \geq \lambda_{\max}(B)$ while $\rho(B) + \frac{k}{D} \leq \frac{r}{Q} + \frac{6\ell+1}{6Q} \leq \frac{5}{6}$. Appending k external jobs of deadline D yields a Pinwheel instance of total density $\leq \frac{5}{6}$—hence feasible by Kawamura's theorem [3]—yet in any feasible schedule the k external jobs must occupy a limiting fraction $\geq \frac{k}{D} > \lambda_{\max}(B)$ of slots unused by B, a contradiction.

(2) For $(2, 2m)$, the $2m$-periodic schedule $(1, _)^{m-1}, (1, 2)$ achieves $\lambda = \frac{m-1}{2m} = 1 - \rho(2, 2m)$, so excess is 0. For $(2, 2m+1)$, let $f : \mathbb{Z} \to \{0, 1, 2\}$ be any bi-infinite feasible schedule. Because job 1 has deadline 2, every adjacent pair $\{t, t+1\}$ contains job 1, so by induction on m (Lean `thm05`) any $2m$-window $[a, a + 2m)$ contains at most m non-1 slots. Suppose $[a, a + 2m)$ contained $\geq m$ idle (0) slots. Then it must contain *exactly* m idle slots and m copies of job 1 (hence zero copies of job 2). Moreover, the $2m - 2$ interior slots $\{a+1, \ldots, a+2m-2\}$ partition into $m-1$ disjoint adjacent pairs, each containing at least one copy of job 1, so the interior holds at most $m-1$ idle slots (Lean `thm05` at $m-1$). Therefore at least one boundary slot of $[a, a+2m)$ must be idle: if a is idle, job 1's deadline 2 forces $a-1$ to be job 1, so the $(2m+1)$-window $[a-1, a+2m)$ contains zero copies of job 2; if $a+2m-1$ is idle, slot $a+2m$ is forced to be job 1, so $[a, a+2m+1)$ contains zero copies of job 2. Either way, job 2's deadline $2m+1$ is violated. Thus every $2m$-window has $\leq m-1$ idle slots, proving $\lambda_{\max}(2, 2m+1) \leq \frac{m-1}{2m}$. Achievability by $(1, _)^{m-1}, (1, 2)$ (Lean `thm07`) and the exact rational identity $(1 - \frac{m-1}{2m}) - (\frac{1}{2} + \frac{1}{2m+1}) = \frac{1}{2m(2m+1)}$ (Lean `thm06`) complete the proof. □

4 Minimality of C_5 and Pareto-Optimal Prime Assignments

Stage 2 of [1] eliminates breaks by encoding two-hour tests via five witness jobs of periods $d_g c_v$ with $(c_0, \ldots, c_4) = (14, 33, 10, 21, 55)$ (equivalently $(10, 55, 33, 21, 14)$ in non-edge cycle order) and $K = 2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 = 2310$, padded by $2K - \sum_v K/c_v = 4002$ rigid fillers. We prove this graph and modulus are provably minimal and uncover strictly sharper prime assignments.

Theorem 4.1 (C_5 Minimality and Exact Pareto Frontier Across All $5! = 120$ Prime Bijections)**.** *Consider width-2 rigid-vs-moving separation gadgets formed by assigning primes p_e to non-edges of a graph $G = (V, E)$ with $c_v = \prod_{e \ni v} p_e$ and $K = \prod_e p_e$:*



Figure 2: (a) Exact lifted density ceiling $\rho+\lambda_{\max} = 1-\frac{1}{2m(2m+1)}$ for $(2, 2m+1)$ versus zero-excess $(2, 2m)$ and the Kawamura-dual barrier 5/6 (Theorem 3.1). (b) Exact forced-occupancy excess $\Phi(2, 2m+1) = \frac{1}{2m(2m+1)}$.

1. ***Unique Minimality of*** C_5 ***and*** $K = 2310$ ***(Lean*** `thm15`***, Cert.*** `C10`***):*** *Any graph with* $\omega(G) \le 2 < \chi(G)$ *has* $|V| \ge 5$*, with unique 5-vertex minimizer* $G \cong C_5$ *(5 non-edges). Since every prime* p *must label an independent set of size* $\le \alpha(C_5) = 2$ *(at most one non-edge), at least* 5 *distinct primes are required, so* $K \ge 2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 = 2310$ *is sharp.*

2. ***Exact Pareto Frontier Over All*** 120 ***Bijections (Lean*** `thm16`***–***`thm17`***, Certs.*** `C09`***,*** `C11`***):*** *Across all* $5! = 120$ *assignments* $(p_0, \ldots, p_4)$ *of* $\{2, 3, 5, 7, 11\}$ *to the non-edge 5-cycle of* C_5 *(with* $c_v = p_v p_{v+1}$*, indices mod* 5*):*

   - Fotakis et al. [1]: *non-edge primes* $[2, 5, 11, 3, 7] \implies c_v = (10, 55, 33, 21, 14)$, $\sum 1/c_v = \frac{103}{385}$, 4002 *fillers,* $\max c_v = 55$.
   - Filler-optimal: *non-edge primes* $[2, 3, 7, 11, 5] \implies c_v = (6, 21, 77, 55, 10)$, $\sum 1/c_v = \frac{19}{55}$, **3822** *fillers (saving* **180** *jobs per two-hour test), CRT phases* $(4, 15, 56, 11, 5)$.
   - Period-optimal: *non-edge primes* $[2, 5, 7, 3, 11] \implies c_v = (10, 35, 21, 33, 22)$, $\sum 1/c_v = \frac{97}{385}$, 4038 *fillers,* $\max \mathbf{c_v} = \mathbf{35}$ *(−20 vs. 55), CRT phases* $(6, 15, 7, 12, 11)$.

Proof. (1) Exhaustive check over all graphs on ≤ 4 vertices confirms every triangle-free graph on ≤ 4 vertices is bipartite (Cert. `C10`), whereas C_5 is triangle-free ($\omega = 2$) and non-2-colorable (Lean `thm15`, $\chi = 3$). Because $\alpha(C_5) = 2$, no three vertices are mutually non-adjacent, so any prime factor shared by three vertices would suppress a colliding edge pair; thus distinct primes are required for all 5 non-edges, forcing $K \ge 2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 = 2310$.

(2) For any bijection $(p_0, \ldots, p_4)$ of $\{2, 3, 5, 7, 11\}$ onto the 5-cycle of non-edges of C_5 with $c_v = p_v p_{v+1}$ (indices modulo 5), choosing phases $\beta_v \equiv 0 \pmod{p_v}$ and $\beta_v \equiv 1 \pmod{p_{v+1}}$ via the Chinese Remainder Theorem ensures $\beta_v \equiv 1 \not\equiv 0 \equiv \beta_{v+1} \pmod{p_{v+1}}$ on the shared prime p_{v+1} of every non-edge $\{v, v+1\}$, so no non-adjacent vertices ever coincide on any day $t \in \mathbb{Z}/2310\mathbb{Z}$, capping daily collisions at $\omega(C_5) = 2$ (verified exhaustively across all $t \in \{0, \ldots, 2309\}$ in Lean `thm16`). Exhaustive evaluation of 'fillersOf' and 'maxCvOf' across all 120 permutations in Lean `thm17` certifies exact minima 3822 and 35. □

5 Exact Slack Conservation and the Minimal 5-Slot $(3, 4, 4, d)$ Obstruction

Finally, we record the exact Stage 1/2 saturation and width identities alongside a sharp local infeasibility witness approaching $\frac{5}{6}^+$ with all deadlines ≥ 3.



Figure 3: (a) Exact Pareto frontier across all $5! = 120$ bijections of $\{2, 3, 5, 7, 11\}$ onto the non-edges of C_5, showing our filler-optimal (3822 vs. 4002) and period-optimal ($\max c_v = 35$ vs. 55) assignments (Theorem 4.1). (b) Infeasible family $(3, 4, 4, d)$ with all deadlines ≥ 3 and density $\frac{5}{6} + \frac{1}{d} \to \frac{5}{6}^+$ (Theorem 5.1).

Theorem 5.1 (Exact Reduction Identities and Minimal 5-Slot Obstruction for $(3, 4, 4, d)$). *1.* ***Stage 1/2 Conservation & Two-Sided Slack (Lean `thm01`–`thm04`, Certs. `C12`, `C15`):*** *In Stage 1 of [1] (N variables, m clauses), the $4N + 5$ jobs achieve exact saturation $|S_t| = 4N + 3$ with break ratio $\frac{4N+3}{72N+15} \in (\frac{1}{18}, \frac{7}{87}]$, and Stage 2 yields exact break-free width $w' = (32m+128)(72N+15) + 24m + 95$. In any c-gate lifting (Theorem 2.2), the slack $\sigma := (\rho(G) + \frac{1}{c}) - \rho(P_G(\mathcal{D}))$ satisfies*

$$\frac{c\sum_{i=1}^{n} \delta_i/b_i^2}{T(T + c\Delta)} \leq \sigma = \sum_{i=1}^{n} \frac{c\delta_i}{Tb_i(Tb_i + c\delta_i)} \leq \frac{c\sum_{i=1}^{n} \delta_i/b_i^2}{T^2} \leq \frac{nc\Delta}{T^2}. \tag{3}$$

2. ***Minimal 5-Slot Obstruction for $(3, 4, 4, d) \to \frac{5}{6}^+$ (Lean `thm18`–`thm19`, Certs. `C13`–`C14`):*** *While $(3, 4, 4)$ has density $\frac{5}{6}$ and period-3 schedule `1,2,3`, the family $(3, 4, 4, d)$ ($\rho = \frac{5}{6} + \frac{1}{d} \to \frac{5}{6}^+$, all deadlines ≥ 3) is infeasible for every $d \geq 1$. Moreover, infeasibility is witnessed locally on the 5-slot window $\{-2, -1, 0, 1, 2\}$ (minimal: every 4-slot subwindow containing 0 is satisfiable, e.g. $(2, 4, 1, 3)$ on $\{-1, 0, 1, 2\}$ and $(3, 1, 4, 2)$ on $\{-2, -1, 0, 1\}$), contrasting with the 3-slot window $\{-1, 0, 1\}$ for $(2, 3, d)$.*

Proof. Part (1) follows immediately from $w = 72N + 15$, $M = 8m + 32$, $w' = 4Mw + 3M - 1$, and $Tb_i \leq Tb_i + c\delta_i \leq b_i(T + c\Delta)$ (Lean `thm01`–`thm04`). For Part (2), in any bi-infinite schedule of $(3, 4, 4, d)$, job 4 must appear at some slot (shifted to 0). On the four remaining slots $\{-2, -1, 1, 2\}$ of the 5-slot window $\{-2, -1, 0, 1, 2\}$, job 1 (deadline 3) must hit all three 3-windows $\{-2, -1, 0\}$, $\{-1, 0, 1\}$, $\{0, 1, 2\}$, while jobs 2 and 3 (deadline 4) must each hit both 4-windows $\{-2, -1, 0, 1\}$ and $\{-1, 0, 1, 2\}$. Exhaustive verification over all $4^4 = 256$ assignments in Lean `thm19` (and Cert. `C13`) proves zero valid assignments exist, whereas on every 4-slot window containing 0 a valid assignment exists—specifically $(-1, 0, 1, 2) = (2, 4, 1, 3)$ hits both 3-windows $\{-1, 0, 1\}, \{0, 1, 2\}$ with job 1 and the 4-window with jobs 2, 3 (and symmetrically $(-2, -1, 0, 1) = (3, 1, 4, 2)$), proving 5 slots is minimal. □

6 Formal Verification Architecture and Reproducibility

All results are independently verified across three layers:

1. **Constructive Lean 4.36.0 Formalization:** 20 theorems (`thm01`–`thm20`) in `lean/PinwheelGateLifting.lean` compiling under `lean -DwarningAsError=true` with zero external imports, zero `sorry`,

zero `grind`, and zero `Classical.choice`, including full kernel verification of the 840-state automaton for $G_4 = (3, 4, 7, 10)$, all 120 C_5 prime bijections, $\mathbb{Z}/2310\mathbb{Z}$ phase disjointness, and the 256-case 5-slot $(3, 4, 4, d)$ obstruction.

2. **AST-Audited Zero-Float Python Verifier:** Pure standard-library code (`int`, `Fraction`) in `verification/verify_pinwheel_gates.py`, self-auditing its AST and emitting 16 canonical SHA-256 certificates (`C01`–`C16`) across four modes (manifest digest `e24fa9a1dc7a7ce7...`).
3. **Adversarial Test Suite:** 56 pytest checks in `tests/test_adversarial.py` covering positive verification and live adversarial tampering across all four modes.

AI Assistance Disclosure. Portions of the finite-state gate discovery, Lean 4 formalization, zero-float verification tooling, and manuscript preparation were developed using Google Antigravity. All theorems, formal proofs, exact rational certificates, and adversarial tests were independently audited and verified, and the author takes full responsibility for all mathematical content.

References

[1] Dimitris Fotakis, Sotiris Kanellopoulos, Giorgos Mitropoulos, Aris Pagourtzis, Christos Papadimitriou, Christos Pergaminelis, and Thanos Tolias. Pinwheel scheduling is PSPACE-complete. *arXiv preprint arXiv:2611.34869v1*, November 2026.

[2] Robert Holte, Aloysius Mok, Louis Rosier, Igor Tulchinsky, and Donald Varvel. The pinwheel: A real-time scheduling problem. In *Proceedings of the 22nd Annual Hawaii International Conference on System Sciences (HICSS)*, volume 2, pages 693–702, 1989.

[3] Akitoshi Kawamura. Proof of the density threshold conjecture for pinwheel scheduling. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC)*, pages 1816–1819, 2024.

[4] Robert Kleinberg and Ahan Mishra. NP-hardness and a PTAS for the pinwheel problem. In *Proceedings of the 67th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, 2026. arXiv:2604.13974.

[5] Yusuke Kobayashi, Bingkai Lin, and Joseph Swernofsky. Dense pinwheel packing is strongly NP-complete. *arXiv preprint arXiv:2609.20075*, 2026.

[6] James B. Orlin. The complexity of dynamic languages and dynamic optimization problems. In *Proceedings of the 13th Annual ACM Symposium on Theory of Computing (STOC)*, pages 218–227, 1981.