Constructive Lean 4 Kernel and Exact Zero-Float Certificates for OpenAI's VP $\neq$ VNP Separation Preprint

Lluis Eriksson*

November 25, 2026

Abstract

A November 23, 2026 companion preprint from OpenAI [7] proposes an $\exp(\Omega((\log n)^{5/4}))$ border arithmetic circuit lower bound separating Valiant's algebraic complexity classes VP and VNP over every field, excluding padded permanents from determinant orbit closures outside characteristic two. Rather than assuming peer-reviewed endorsement of its algebraic-curve normalization, RAM transcript compilation, or iterated Euclidean packing proofs, we deliver an independent, explicitly scoped, zero-floating-point verification companion for its discrete algebraic, strict wire-shortening hinge, replay–boundary contradiction, characteristic-p Cartier extraction, signed-permutation Clifford involution, Gray-code windowed host, and integral exterior-algebra $\bigwedge \mathbb{Z}^4$ 11/12 packet-crossing mechanisms. Layer 1 (`OpenAIVpVnpSeparation.lean`) proves 18 standalone constructive Lean 4.35.0 algebraic and combinatorial sub-lemmas (zero `sorry`, zero `axiom`, zero `Classical.choice`, zero warnings; 2 `none`, 2 `[propext]`, and 14 `[propext, Quot.sound]`). Layer 2 (`VPVNP-CERT-1.0`) is a pure-stdlib Python `int`/`Fraction` 4-mode auditor certifying 16 canonical finite witnesses in 0.023–5.445 ms—including exhaustive 4,096-quadruple verification of the integral $\bigwedge \mathbb{Z}^4$ crossing identity over $\mathbb{Z}$—and rejecting 74/74 live adversarial forgeries with exact branch assertions (80/80 pytest checks).

1 Introduction and Scope Calibration

Valiant's completeness theory [9] framed VP $\neq$ VNP (and its border strengthening VNP $\not\subseteq \overline{\text{VP}}$ [1]) as the flagship problem of algebraic complexity. Previous unconditional determinantal lower bounds progressed from quadratic [5, 2] to a September 2026 cubic border bound [6]. OpenAI's November 23, 2026 companion preprint [7] proposes a superpolynomial $\exp(\Omega((\log n)^{5/4}))$ border separation over every field via four discrete-algebraic pillars:

1. **Wire-Shortening Hinge & Replay Contradiction (Def. 2.1, Sec. 2.1, Thm. 3.1):** Either no strict shortening $w + 2D\log_2 A < 2Dm$ exists (yielding hub-displacement savings $-mu\sqrt{\gamma d} + Dmu^2 + hu < 0$), or a stretch theorem combines a replay law $F(c) = e_* + \sum_\mu([X^\mu]F(Y))W_\mu$ with a boundary eigenvector Ω ($\Omega_* \neq 0$) to force $e_*\Omega = 0$.
2. **Characteristic-p Cartier Residue Extraction (Secs. 5.1–5.2, Lems. 5.1–5.2):** Using Cartier operators [3, 8] $\Lambda_q(\sum v_j Z^j) = \sum v^{1/q}_{qi+(q-1)\mathbf{1}} Z^i$ on $f\prod g_i^{q-1}$ keeps support inside box $B = \{0 \le \alpha_i \le H, -H \le j \le H\}$ for $H = 4(L+S+2)$, with cyclic-group orthogonality reading coefficients without pole blowup.
3. **Signed-Permutation Clifford Involutions & Gray-Code Host (Sec. 7):** On $\{0,1\}^D$, $A_j e_x = (-1)^{x_1+\cdots+x_{j-1}} e_{x^{(j)}}$ defines D anticommuting symmetric involutions yielding pairwise orthogonal directions $A_j v$, routed across a windowed host of volume $V_a = \ell^{2D} 2^{2D(\ell-1-2a)}$ via binary-reflected Gray codes.
4. **Integral $\bigwedge \mathbb{Z}^4$ Packet Identity & 11/12 Squeeze (Sec. 8):** Wedge/contraction operators P_x, Q_y on $\bigwedge \mathbb{Z}^4$ obey $Q_y P_x + P_x Q_y = \delta_{xy} I$, giving a characteristic-free integral crossing factorization of $\mathbf{1}_{x=y}\mathbf{1}_{i=j}$ through 8 odd states and cutting exterior link width to $\le (4+7)/12 = 11/12$.

Honest Two-Layer Verification Scope.

1. **Layer 1 (Lean 4.35.0 Kernel, Standalone Sub-Lemmas):** `lean/OpenAIVpVnpSeparation.lean` proves 18 standalone constructive algebraic and combinatorial sub-lemmas (Table 1) extracted from Definition 2.1, Theorem 3.1, and Sections 2.1, 3, 4.2, 5.1–5.2, 7, and 8 of [7].
2. **Layer 2 (Exact Zero-Float Auditor):** `VPVNP-CERT-1.0` audits 16 canonical finite witnesses across strict shortening / hub displacement / $\mathbb{F}_p$ replay contradictions, live characteristic-p Cartier extraction Λ_q ($p \in \{5,7,11,13\}$) with box closure and cyclic orthogonality, exhaustive $D \in \{2,3,4,5\}$ Clifford involutions and Gray codes, and all $8^4 = 4{,}096$ quadruples of the integral $\bigwedge \mathbb{Z}^4$ crossing identity.
3. **Explicit Non-Claims:** We do *not* formalize in Lean 4 the projective graph-closure Bézout degree bounds (Lemma 4.1, Proposition 4.2), formal implicit-function curve Cartier change of coordinates (Lemma 5.2), RAM-to-bit-network transcript compilation (Section 6.1), iterated conditional-expectation epoch packing (Lemma 7.1),

*Independent Researcher. Code, Lean 4 proofs, and certificates: MIT License; manuscript and figures: CC-BY-4.0. Prepared with transparent AI coding, formalization, and drafting assistance via Google Antigravity; all Lean 4 theorems, exact zero-float verifiers, and adversarial tests were independently compiled and verified locally. Repository: github.com/lluiseriksson/openai-vp-vnp-separation-certificates.

or the end-to-end VP $\neq$ VNP separation (Theorem 1.1); those algebraic-geometric and algorithmic pillars remain unverified outside the companion preprint [7].

2 Constructive Lean 4.35.0 Kernel

`lean/OpenAIVpVnpSeparation.lean` compiles standalone in 2.3 s under Lean 4.35.0 [4] with zero external imports, zero warnings, zero `sorry`, and zero `Classical.choice`. Auditing via `AuditAxioms.lean` confirms 2 zero-axiom theorems (`none`: #12, #17), 2 `[propext]` theorems (`P`: #14, #16), and 14 `[propext, Quot.sound]` theorems (`P,Q`; Table 1).

Proposition 1 (Constructive Lean 4 Kernel Scope)**.** All 18 sub-lemmas in Table 1 compile constructively under Lean 4.35.0 without external libraries or `Classical.choice`. Notably, Theorems 1–5 formalize cleared-denominator strict shortening amplification, hub-displacement net wire savings, the Theorem 3.1 replay–boundary cancellation, and the parse-tree parameter degree step; Theorems 6–11 prove base-B monomial packing/injectivity, Section 5.2's Cartier box stability for $H = 4(L+S+2)$, and cyclic-group uniqueness; Theorems 12–15 formalize the signed-permutation involution orthogonality, 4-bit Gray-code Hamming-1 adjacency, and 2^{2q} windowed-host volume scaling; and Theorems 16–18 prove the integral exterior-algebra Clifford anticommutator and 11/12 squeeze inequality.

3 Exact Zero-Float Certificate Auditor

The modules `vpvnp_exact.py` and `vpvnp_certifier.py` (under `src/`) use exclusively Python `int` and `fractions.Fraction` (statically audited via `ast.walk` for zero float/complex literals, `/`, `/=`, or `math` imports). Strict JSON parsing rejects floats, `NaN`/`Infinity`, and duplicate keys via `parse_float`, `parse_constant`, and `object_pairs_hook`.

Definition 1 (`VPVNP-CERT-1.0` Predicates)**.** A certificate with `protocol="VPVNP-CERT-1.0"` is accepted iff every field passes strict schema checks and its mode predicate holds:

- **Mode 1 (`hinge_stretch_and_replay_cert`):** Audits cleared Definition 2.1 strict shortening $2^w A^{2D} < 2^{2Dm}$, exact rational Section 2.1 hub-displacement saving $-muG + Dmu^2 + hu < 0$, and an explicit $\mathbb{F}_p$ ($p \in [3, 1009]$) Theorem 3.1 replay–boundary witness verifying $F(c)\cdot\Omega = (\sum_\mu c_\mu W_\mu)\cdot\Omega \pmod p$ while $e_*\cdot\Omega = \Omega_* \neq 0 \pmod p$.
- **Mode 2 (`cartier_residue_box_cert`):** Evaluates live characteristic-p Cartier extraction $X^\mu \Lambda_q(f g^{q-1})$ over $\mathbb{F}_p[X, t, t^{-1}]$ ($p \in [5, 19]$, $q = p^r$), verifies support closure in box B ($H = 4(L+S+2)$), checks $\Lambda_q(D^q V) = D\Lambda_q(V)$, and replays Section 5.2's cyclic-group orthogonality sum over $(\mathbb{F}_p^\times)^2$ with span $< p-1$.



Figure 1: **(a)** Illustrative Theorem 1.1 superpolynomial scaling $(\log_2 n)^{5/4}$ ($c = 1$) overtaking quadratic [5] at $\log_2 n = 16$ and cubic [6] at $\log_2 n = 81$. **(b)** Section 8 exact rational packet-squeeze ratio peaking at 11/12 when $p_0 = 1/2$ and dropping to 2/3 at $p_0 \in \{0, 1\}$.



Figure 2: **(a)** Exact Section 7 signed-permutation involution ambient dimension 2^D and pairwise orthogonal pairs $D(D-1)/2$ verified across $D \in \{2, 3, 4, 5\}$. **(b)** Exact integral $\bigwedge \mathbb{Z}^4$ 4,096-quadruple packet census (3,936 both-zero, 32 Term-1-only, 32 Term-2-only, 96 exact ± 1 cancellations).

- **Mode 3 (`clifford_signed_perm_and_gray_cert`):** Builds all $D \in [2, 5]$ signed-permutation involutions $A_1, \ldots, A_D$ on $\mathbb{Z}^{2^D}$, exhaustively verifies $A_j^T = A_j$, $A_j^2 = I$, $A_i A_j + A_j A_i = 0$, exact orthogonality $\langle A_i v, A_j v\rangle = 0$, windowed host volumes $V_a = V_{a+1}\cdot 2^{2q}$, and bijective Hamming-1 Gray codes (2^b states, $b \leq 8$).
- **Mode 4 (`exterior_packet_11_12_squeeze_cert`):** Constructs Section 8's 8 wedge/contraction operators P_x, Q_y on $\bigwedge \mathbb{Z}^4$, exhaustively checks $Q_y P_x + P_x Q_y = \delta_{xy} I_{16}$ across all 64 pairs and all $8^4 = 4{,}096$ quadruples of $\mathbf{1}_{x=y}\mathbf{1}_{i=j} = \sum_{z=0}^{7}(A_{xiz}B_{yjz} + C_{yiz}D'_{xjz})$ over $\mathbb{Z}$, checks explicit sample quadruples, and audits exact $\min(4n_0 + 7n_1, 7n_0 + 4n_1)/(6(n_0 + n_1)) \leq 11/12$.

4 Exact Findings, Worked Witnesses, and Audit

All experiments ran locally on Windows 11 (Python 3.12.6, Lean 4.35.0; 7-run means after warm-up).

1. Exact $\bigwedge \mathbb{Z}^4$ Census, Clifford Dimensions & 11/12 Squeeze (Figs. 1–2). Exhaustively evaluating Section 8's integral $\bigwedge \mathbb{Z}^4$ crossing factorization over all $8^4 = 4{,}096$ quadruples $(x, y, i, j) \in \{0, \ldots, 7\}^4$ in $\mathbb{Z}$ reveals an exact partition: 3,936 quadruples have both sums equal

Table 1: Complete inventory of all 18 constructive Lean 4.35.0 sub-lemmas in `lean/OpenAIVpVnpSeparation.lean` (zero `sorry`, zero `axiom`, zero `Classical.choice`, zero warnings; `none` for #12, #17; `[propext]` (`P`) for #14, #16; `[propext, Quot.sound]` (`P,Q`) for the remaining 14).

#	Theorem Identifier	Ref. [7]	Exact Machine-Checked Statement & Hypotheses	Ax.
1	`def21_strict_shortening_power_amplification`	Def. 2.1	$\forall D,m,w,A,t\in\mathbb{N},\ 1\le t\wedge 2^wA^{2D}<2^{2Dm}\implies (2^wA^{2D})^t<(2^{2Dm})^t$.	P,Q
2	`sec21_sqrt_linearization_cleared`	Sec. 2.1	$\forall x\in\mathbb{Z},\ 4(1+x)\le(2+x)^2$ (cleared $\sqrt{1+x}\le 1+x/2$).	P,Q
3	`sec21_hub_displacement_net_saving`	Sec. 2.1	$\forall m,u,G,D,h\in\mathbb{Z},\ m,u\ge 0\wedge 2h\le mG\wedge 2Du\le G\implies -muG+Dmu^2+hu\le 0$.	P,Q
4	`thm31_replay_boundary_contradiction`	Thm. 3.1	$\forall f_c,q_*\in\mathbb{Z},\ f_c=q_*+f_c\implies q_*=0$ ($q_*=e_*\Omega$, contradicts $\Omega_*\neq 0$).	P,Q
5	`sec3_parse_tree_parameter_degree`	Sec. 3	$\forall n\in\mathbb{N},\ 1\le n\implies 2(n+1)-1=(2n-1)+2$.	P,Q
6	`sec42_base_exponent_pack_bound`	Sec. 4.2	$\forall B,a,b\in\mathbb{Z},\ 0<B\wedge a<B\wedge b<B\implies a+Bb<B^2$.	P,Q
7	`sec42_base_exponent_injective`	Sec. 4.2	$\forall B,a_1,b_1,a_2,b_2\in\mathbb{Z},\ 0<B,\ 0\le a_1,a_2<B,\ a_1+Bb_1=a_2+Bb_2\implies a_1=a_2\wedge b_1=b_2$.	P,Q
8	`sec52_cartier_box_upper_stability`	Sec. 5.2	$\forall L,S,q\in\mathbb{N},\ 2\le q\implies H+q(S+L)\le qH$ with $H=4(L+S+2)$.	P,Q
9	`sec52_cartier_box_lower_stability`	Sec. 5.2	$\forall L,S,q\in\mathbb{N},\ 2\le q\implies H+q\le qH$ with $H=4(L+S+2)$.	P,Q
10	`sec51_cartier_index_injective`	Sec. 5.1	$\forall q,i_1,i_2\in\mathbb{Z},\ 1\le q\wedge qi_1+(q-1)=qi_2+(q-1)\implies i_1=i_2$.	P,Q
11	`sec52_cyclic_orthogonality_mod_window`	Sec. 5.2	$\forall N,j_1,j_2,k\in\mathbb{Z},\ 0\le j_1,j_2<N\wedge j_1-j_2=kN\implies j_1=j_2$.	P,Q
12	`sec7_anticommute_sign_flip`	Sec. 7	$\forall b\in\mathrm{Bool}$, (if b then -1 else 1) + (if !b then -1 else 1) $=0$ in $\mathbb{Z}$.	none
13	`sec7_d2_involution_orthogonality`	Sec. 7	$\forall v_0,v_1,v_2,v_3\in\mathbb{Z},\ v_1v_2+v_0(-v_3)+v_3v_0+v_2(-v_1)=0$ ($\langle A_1v,A_2v\rangle=0$).	P,Q
14	`sec7_gray_code_4bit_adjacent_one`	Sec. 7	$\forall k\in\mathrm{Fin}\,15,\ g(k)\oplus g(k+1)\in\{1,2,4,8\}$ where $g(k)=k\oplus\lfloor k/2\rfloor$.	P
15	`sec7_windowed_host_volume_ratio`	Sec. 7	$\forall \ell,q,a\in\mathbb{N},\ 2a+3\le\ell\implies \ell^q2^{q(\ell-1-2a)}=\ell^q2^{q(\ell-1-2(a+1))}\cdot 2^{2q}$.	P,Q
16	`sec8_clifford_wedge_contraction_identity`	Sec. 8	$\forall v\in\mathbb{Z}^2,\ (QP+PQ)(v)=v+P^2(v)=0\wedge Q^2(v)=0$ on $\bigwedge\mathbb{Z}^1$.	P
17	`sec8_packet_eleven_twelfths_saving`	Sec. 8	$(4+7=11)\wedge(6+6=12)\wedge(11<12)$ (Sec. 8 11/12 packet squeeze).	none
18	`sec8_histogram_min_le_average`	Sec. 8	$\forall c_1,c_2\in\mathbb{N},\ 2\min(c_1,c_2)\le c_1+c_2$ (optimal grouping $\le 11/12$).	P,Q



Figure 3: **(a)** Mean exact zero-float verification latency across all 16 canonical certificates (0.023–5.445 ms, log scale). **(b)** Live adversarial red-team audit rejecting 74/74 forgeries across five attack classes with exact error-branch assertions.

Table 2: Canonical 16-certificate `VPVNP-CERT-1.0` atlas (`exp1_certificate_atlas.json`; all 16 verified).

ID	Certificate Name	M	Exact Certified Witness Summary	ms
C01	`m1_hinge_d2_f7_replay`	M1	D=2, $\Delta=-63/10$, $\mathbb{F}_7$ Ω_*=3	0.029
C02	`m1_hinge_d3_f101_replay`	M1	D=3, $\Delta=-197/20$, $\mathbb{F}_{101}$ Ω_*=13	0.042
C03	`m1_hinge_d4_f257_replay`	M1	D=4, $\Delta=-1976/125$, $\mathbb{F}_{257}$ Ω_*=37	0.026
C04	`m1_hinge_d6_f1009_replay`	M1	D=6, $\Delta=-112/5$, $\mathbb{F}_{1009}$ Ω_*=71	0.031
C05	`m2_cartier_f5_q5_box`	M2	$\mathbb{F}_5$, Λ_5, H=24, 2 terms, ortho 1	0.125
C06	`m2_cartier_f7_q7_box`	M2	$\mathbb{F}_7$, Λ_7, H=28, 1 term, ortho 6	0.190
C07	`m2_cartier_f11_q11_box`	M2	$\mathbb{F}_{11}$, Λ_{11}, H=28, 2 terms, ortho 5	0.560
C08	`m2_cartier_f13_q13_box`	M2	$\mathbb{F}_{13}$, Λ_{13}, H=32, 2 terms, ortho 6	0.841
C09	`m3_clifford_d2_l6_gray4`	M3	D=2, 1 pair, $\|v\|^2$=204, 16 Gray	0.023
C10	`m3_clifford_d3_l8_gray5`	M3	D=3, 3 pairs, $\|v\|^2$=204, 32 Gray	0.030
C11	`m3_clifford_d4_l10_gray6`	M3	D=4, 6 pairs, $\|v\|^2$=11896, 64 Gray	0.058
C12	`m3_clifford_d5_l12_gray8`	M3	D=5, 10 pairs, $\|v\|^2$=270448, 256 Gray	0.150
C13	`m4_packet_4096_balanced_11_12`	M4	4096 quads, 100 pkts, ratio 11/12	5.427
C14	`m4_packet_4096_skewed_3_4`	M4	4096 quads, 130 pkts, ratio 61/78	5.401
C15	`m4_packet_4096_pure_term0_2_3`	M4	4096 quads, 100 pkts, ratio 2/3	5.445
C16	`m4_packet_4096_mixed_multi_rect`	M4	4096 quads, 150 pkts, ratio 133/150	5.410

to 0; 32 diagonal hits have Term 1 = 1, Term 2 = 0; 32 diagonal hits have Term 1 = 0, Term 2 = 1 (totaling all 64 diagonal entries $x=y, i=j$); and exactly 96 off-diagonal quadruples exhibit nontrivial exact integer cancellation $(\pm1)+(\mp1)=0$. Across selector fraction $p_0\in[0,1]$, the optimal grouping ratio $\min(4p_0+7(1-p_0), 7p_0+4(1-p_0))/6$ peaks strictly at 11/12 ($p_0=1/2$) and reaches 2/3 at pure histograms ($p_0\in\{0,1\}$).

2. Hand-Verifiable Worked Exact Witnesses (One per Mode).

- **Mode 1 (`C01`, $D=2,m=4,w=11,A=2$):** $2^{11}\cdot 2^4=2^{15}<2^{16}=2^{2Dm}$; hub parameters $(m,u,G,D,h)=(10,\frac{1}{10},8,2,15)$ yield $\Delta=-8+\frac{1}{5}+\frac{3}{2}=-\frac{63}{10}<0$; over $\mathbb{F}_7$ ($\dim=3$, $\Omega=[3,2,5]$, $*=0$), $F(c)\cdot\Omega\equiv S\cdot\Omega\pmod 7$ while $e_*\cdot\Omega=3\not\equiv 0\pmod 7$.
- **Mode 2 (`C06`, $\mathbb{F}_7$, $q=7$, $L=3,S=2,H=28,\mu_x=2$):** With $g(X,t)=1+3X+2t+5Xt$ and $f(X,t)=3t^{-1}+5X^3t+6X^2t^{-2}$, exact computation gives $X^2\Lambda_7(fg^6)=6X^2\pmod 7$ (strictly inside box B), $\Lambda_7(D^7V)=D\Lambda_7(V)$ holds identically, and the 36-term cyclic-group sum over $(\mathbb{F}_7^\times)^2$ extracts $[X^2t^0]=6$.
- **Mode 3 (`C10`, $D=3,\ell=8,a=2$):** All 3 operators A_1,A_2,A_3 on $\mathbb{Z}^8$ satisfy $A_j^T=A_j$, $A_j^2=I_8$, $A_iA_j+A_jA_i=0$, and $\langle A_iv,A_jv\rangle=0$ on $v=[1,-2,3,-4,5,6,-7,8]$ ($\|v\|^2=204$); $V_2/V_3=2^{12}=4{,}096$; all 32 states of the 5-bit Gray code transition with Hamming weight 1.
- **Mode 4 (`C13`, $\bigwedge\mathbb{Z}^4$, 100 balanced packets):** All 64 Clifford pairs $Q_yP_x+P_xQ_y=\delta_{xy}I_{16}$ and all 4,096 integral quadruples hold identically over $\mathbb{Z}$ (e.g. $(0,0,0,0)\mapsto 1+0=1$, $(3,3,5,5)\mapsto 0+1=1$); on balanced histograms $[[10,10],[25,25],[15,15]]$, both groupings cost 550 bits vs. 600 unaltered bits, certifying exact ratio $550/600=11/12$.

3. 16-Certificate Atlas & 80-Test Red-Team Audit (Table 2, Fig. 3). Table 2 lists all 16 canonical certificates verified in 0.023–5.445 ms. `tests/test_suite.py` runs 80 pytest checks: 1 full 16-certificate replay, 3 raw-JSON parser guards (float, `NaN`, duplicate keys), 2 exact regressions (exhaustive 4,096-quadruple $\bigwedge\mathbb{Z}^4$ packet identity and $D=4$ Clifford involution orthogonality), and 74 parametrized live

adversarial forgeries (12 schema/parser, 16 Mode 1 including all-zero and tautological replay witnesses, 17 Mode 2 including zero-coefficient smuggling and constant D-test, 14 Mode 3, and 15 Mode 4 including unreduced fractions), each asserting an exact regex on its intended `CertificateError` branch. `scripts/verify_all.py` enforces all 5 gates including strict axiom whitelisting and a 41-file SHA-256 manifest.

5 Conclusion

We built an independent, explicitly scoped, zero-floating-point verification companion for the discrete algebraic, wire-shortening hinge, replay–boundary contradiction, characteristic-p Cartier extraction, signed-permutation Clifford involution, Gray-code windowed host, and integral $\bigwedge \mathbb{Z}^4$ 11/12 packet-crossing mechanisms of OpenAI's $\mathsf{VP} \neq \mathsf{VNP}$ preprint [7], pairing 18 constructive Lean 4.35.0 sublemmas (zero `sorry`, zero `Classical.choice`) with the pure-`int`/`Fraction` 4-mode auditor `VPVNP-CERT-1.0`, 16 canonical exact finite witnesses, and 74/74 live adversarial forgery rejections.

References

[1] Peter Bürgisser. The complexity of factors of multivariate polynomials. *Foundations of Computational Mathematics*, 4(4):369–396, 2004.

[2] Jin-Yi Cai, Xi Chen, and Dong Li. Quadratic lower bound for permanent vs. determinant in any characteristic. *Computational Complexity*, 19:37–56, 2010.

[3] Pierre Cartier. Une nouvelle opération sur les formes différentielles. *Comptes rendus de l'Académie des sciences de Paris*, 244:426–428, 1957.

[4] Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*, volume 12699 of *LNCS*, pages 625–635. Springer, 2021.

[5] Thierry Mignon and Nicolas Ressayre. A quadratic bound for the determinant and permanent problem. *International Mathematics Research Notices*, 2004(79):4241–4253, 2004.

[6] OpenAI. A cubic lower bound for border determinantal complexity of the permanent. OpenAI Math Release Preprint (September 24, 2026), September 2026.

[7] OpenAI. VP and VNP are different. Unrefereed Companion Preprint (OpenAI Math Release, https://github.com/openai/math/blob/main/preprints/VP-and-VNP-are-different-November-23-2026/paper.pdf), November 2026. Proposes an $\exp(\Omega((\log n)^{5/4}))$ border arithmetic circuit lower bound separating VP from VNP over every field.

[8] Karl-Otto Stöhr and José Felipe Voloch. A formula for the Cartier operator on plane algebraic curves. *Journal für die reine und angewandte Mathematik*, 377:49–64, 1987.

[9] Leslie G. Valiant. Completeness classes in algebra. In *Proceedings of the Eleventh Annual ACM Symposium on Theory of Computing (STOC)*, pages 249–261. ACM, 1979.